

High Speed 2 In 1 Monoblock Rotary Filling And Capping Machine

ISO9001:2000, ISO14001, OHSAS18001,

Non-fumigation Wooden Case inserted Iron

Shelf, Suitable for Long Time Sea Delivery

Basic Information

- Place of Origin:
- Brand Name:
- Certification:

• Price:

- Model Number: GXCC Series

1

T/T

Changzhou, China

60 WORKING DAYS

25SETS/MONTHLY

SS304 Or SS316L

Including

Including

TOM

CE, CO

- Minimum Order Quantity:
 - Negotiable
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

- Material:
- Pneumatic Element:
- lement: Airtac ement: Siemens, Schneider Or Panasonic
- Electronic Element:
- Filling Tank:
- Liquid Level Sensor:
- Highlight:
- 2 In 1 rotary filling and capping machine, Monoblock rotary filling and capping machine, High Speed rotary filler and capper



More Images



Intelligent High Speed Rotary Filling And Capping 2-In-1 Monoblock Machine Major characteristics:

- Integrate filling and capping function, compact structure, save space.
 Weighing type filling, suitable variety kinds of liquid, special for liquid which uneven density or with bubble.
- 3. Change moulds are fast loading type, accurate positioning, change over time only need 10 minutes.
- 4. Magnetic force capping, controllable torque, ensuring that every bottle's capping torque is the same.
- 5. Safety door alarm protection, ensuring the security of operator, integral prevention, more environmental.

Technical parameters

No.	Items	Performance
01	Dimensions	3000mm (L) ×2200mm (W) × 2450mm (H)
02	Filling/ capping head	24-6/20-6
03	Suitable bottle	Diameter: Ф50mm~ Ф180mm height:120mm~350mm (May customized)
04	Packing specification	100ml-1L / 1L-5L (may customize)
05	Production capacity (1L)	1L≧6000 bottles/hour; 4L≧3600 bottles/hour
06	Measurement error	≤±4g
07	power supply	380V;50/60HZ
08	host power	5.5KW
09	Air supply	0.55MPa~0.65MPa clean and stable source of gas supply with gas
10	Air consumption	200L/minute
11	Bottle inlet direction	From left to right





Machine details:

Filling nozzle:

The filling nozzle is designed according to the characteristics of liquid products, and nozzle diameter is based on bottle mouth diameter, high processing accuracy, good sealing, smooth filling and no leakage.





Plc control, the changeover time is within 30 minute, fast loading and unloading.



The pass rate of the screw cap is close to 100%, the torque is adjustable, convenient and fast, and the stability is good. High pass rate: Good versatility: Adopts correct capping type, suitable to the anti-theft cap and straw caps.



The cap sorter can incessantly feed caps to capping machine, match to capping machine



Application products: This filling and capping machine is applicable for various bottles and caps





Packaging & Shipping The machine is packked by non-fumigation wooden case, and for keeping the wooden case more secure, we inserted the iron support inside wooden case, makes it suitable for long-term sea delivery.



Tom's logistic department will load the goods into container directly in Tom factory





No.99, Rulin Town, Jintan District, Changzhou City, Jiangsu Province, China.