₫

Rotary High Speed Pesticide Filling Machine Automatic Powder Filling And **Sealing Machine**

Basic Information

• Place of Origin: Changzhou, China

. Brand Name:

Certification: ISO9001:2000, ISO14001, OHSAS18001,

CE, CO

 Model Number: FJ-210GD/300GD/350GD

Minimum Order Quantity:

Negotiable

Non-fumigation Wooden Case inserted Iron Shelf, Suitable for Long Time Sea Delivery • Packaging Details:

• Delivery Time: 45 WORKING DAYS

• Payment Terms:

• Supply Ability: 25SETS/MONTHLY



Product Specification

Material: SS304 Or SS316L

Pneumatic Element: Airtac

 Electronic Element: Siemens, Schneider Or Panasonic

Powder Hopper: Including

• Filling Material: Powder And Liquid And Granule

4 Sides Sealing • Sealing Style: Packing Style: Horizontal Type

High Speed Pesticide Filling Machine, Rotary Pesticide Filling Machine, Highlight:

SS316L automatic powder filling and sealing



More Images











Product Description

Automatic PLC Control Rotary Pesticide Power Filling And Sealing Machine With High Speed

Major characteristics:

- 1. Mechanical arm bag handling -printing -bag opening -filling -jolt ramming- air pressed -sealing shaping -embossing -outputting
- 2. PLC and Touch screen control panels are used to control the machine automatically. It is easy to operate and no environment pollution .
- 3. The mainframe is adjusted by imported frequency conversion .
- 4. The packaging bags are good-looking, which has been printed and heat-sealed for twice .
- 5. The machine is designed with shaping service position ,so the mouth of the bag is smooth after sealing.
- 6. The part which contacts with filling materials is made of stainless steel. It is clean, anti-corrosion and stable
- 7. According to the requirement of the filling materials, automatic weighing machine, screw filling machine is optional. Intelligent compound balance and other machines are optional for a filling line .

Technical parameters:

| No. | Item | Performance |
|-----|----------------------------------|----------------------|
| 1 | Machine overall dimension(LxWxH) | 3000mm*2600mm*2200mm |
| 2 | Machine weight | 1000KG |
| 3 | Power supply | 380V; 50/60HZ |
| 4 | Power | 4KW/5KW/5.5KW |
| | • | • |

| 5 | Bag size (L*W) | 210GD :100*150-210*320mm |
|---|-------------------|--|
| | | 300GD: 200*180-300*450mm 350GD: 250*230mm-350*500mm |
| 6 | Weighing range | 210GD :50-500g |
| | | 300GD: 500g-2000g |
| | | 350GD: 1kg-5kg |
| 7 | Packing speed | 210GD : 40bags/minute |
| | | 300GD: 10-18bags/minute |
| | | 350GD: 10-15bags/minute |
| 6 | Air source | 0.6MPa clean and compressed air |
| 7 | Air consumption | 40L/min |
| 8 | Suitable bag type | Three sides bag, four sides bags, stand pouch bag |



Machine details:
This machine is suitable for medium and big-sized bag packing, for filling both powder and liquid, small and simple structure, save




This filling part is rotary type with 8 working station, there's two filling nozzle, one filling nozzle is rough filling, the second filling is fine filling, there's weighing scale under filling station to guarantee high filling accuracy.



After filling, there's two sealing plate to seal the bag, one is hot sealing plate to seal the bag firmly, the second is cold sealing plate to make the sealing edge more beautiful



This is the bag feeding part, the people need to put the new empty bags into feeding part manually, usually it can house 200-300pcs of bags



This is the bag outlet conveyor, after filling and sealing, the bag will come out by this conveyor to enter into the next packing station



Here's the different material feeding device, dust collector and other auxiliary machines, can meet different requirements of customers

Auxiliary Machine Series 袋包机辅机及辅助装置 Z型上料机 斗式上料机 上料机 真空包装机

Here's the different material filling hopper and filling tank, if the filling material is powder, then machine will use screw hopper, if the filling material is liquid, then machine will use filling tank, if the filling material is granule or other bulk solid, the machine will use weighing head



Packaging & Shipping
The machine is packked by non-fumigation wooden case, and for keeping the wooden case more secure, we inserted the iron support inside wooden case, makes it suitable for long-term sea delivery.



Tom's logistic department will load the goods into container directty in Tom factory



TemperatureJiangsu TOM Intelligent Equipment Co., Ltd.,

No.99, Rulin Town, Jintan District, Changzhou City, Jiangsu Province, China.